

Specialty Wiring Devices

2655 Napa Valley Corporate Dr., Napa, CA 94558

(707) 226-8600 FAX: (707) 226-9670

Date: May, 2004

Rev: 01

Connector, straight
15A, 250V

Catalog Number: 320IEC15

- Item:** Connector, appliance coupler.
IEC 60320 standard sheet C15.
- Rating:** For hot conditions (120°C rating).
10 amperes, 250 volts ac: International.
15 amperes, 250 volts ac (max): North America.
- Materials:** Plastic parts are heat stabilized nylon with CTI greater than 400 volts.
Contacts are solid brass.
- Contacts:** One piece, .032" thick brass, double wipe.
- Terminals:** Tempered brass, lug style, Perma-Lock™ design.
- Terminal Identification:** Terminal screws are color coded.
Wire entrance holes marked "L", "N" and "⊥".
- Cord Clamp:** Internal. Accommodates 0.300" (18/3 SJ) through
0.655" (12/3 S) North American cable,
And 3 conductor .75 to 4.00 mm² harmonized cable.
- Overall Design:** Two assembly screws, U-drive style.
All screws are combination slot/cross head.
Beveled housing. Dust seal at cord entry.
Cable strip length gauge molded into connector body.
- Listings:** UL listed, CSA certified.
- Dimensions:**

